

# MODEL PP-5336 LIFT & POWERED TURN

**10 Year/250,000 Cycle Warranty**

*These units are optimized lift and turn units used where the lifting and turning functions must be done independently.*

**ISO 9001:2008  
Certified**



Capacity: 5,300 lbs.  
Min. Platform Size: 24 x 48 in.  
Max. Platform Size: 48 x 64 in.  
Lift Table Size: 24 x 48 in.  
Lowered Height: 16 in.  
Raised Height: 52 in.  
Speed Up: 23 sec.  
Internal Motor: 2 HP  
Shipping Weight: 1,165 lbs.



**5,300 lb. Capacity - 36 in. Travel**

## SPECIAL FEATURES & BENEFITS

- ▶ These units are equipped with the patented “Platform Centering Devices”, which doubles or triples lift life.
- ▶ These units are equipped with single internally mounted power units.
- ▶ All of the controllers are Underwriter Laboratory listed assemblies.
- ▶ All hydraulic cylinders are machine grade with clear plastic return lines.
- ▶ All pressure hoses are double wire braid with JIC fittings.
- ▶ These units are fully primed and finished with baked enamel.

**CLICK HERE FOR: [Optional Accessories](#) [Rules For Creating Combinations](#)**

## FEATURE DETAILS



▶ **Platform Centering Device**



▶ **Machine Grade Cylinder**



▶ **Double Wire Braid Hose**



▶ **Power Unit**