

MODEL PT-55364-I LIFT AND TILT COMBINATION

10 Year/250,000 Cycle Warranty

These lift and tilt units are optimized combination designs that are used where the lifting and tilting functions must be done independently.

**ISO 9001:2008
Certified**



Degree of Tilt: 45
 Capacity: 5,500 lbs.
 Min. Platform Size: 30 x 48 in.
 Max. Platform Size: 48 x 60 in.
 Lowered Height: 14.25 in.
 Raised Height: 50.25 in.
 Lift Speed Up: 23 sec.
 Tilt Speed Up: 15 sec.
 Internal Motor: 2 HP
 Shipping Weight: 1,055 lbs.



5,500 lb. Capacity - 36 in. Travel

SPECIAL FEATURES & BENEFITS

- ▶ These units are equipped with the patented “Platform Centering Devices”, which doubles or triples lift life.
- ▶ These units are equipped with single internally mounted power units.
- ▶ All of the controllers are Underwriter Laboratory listed assemblies.
- ▶ All hydraulic cylinders are machine grade with clear plastic return lines.
- ▶ All pressure hoses are double wire braid with JIC fittings.
- ▶ These units are fully primed and finished with baked enamel.

CLICK HERE FOR: [Optional Accessories](#) [Rules For Creating Combinations](#)

FEATURE DETAILS




▶ **Platform Centering Device**



▶ **Machine Grade Cylinder**



▶ **Double Wire Braid Hose**



▶ **Power Unit**