

# MODEL VCM-2 MECHANICAL VRC - CANTILEVER

**5 Year Structural Warranty  
1 Year Electrical**

*These lifts are designed to move goods and materials between multiple floor levels quickly and safely. They may be configured for C, Z, or L loading patterns between floor levels and are available in a wide variety of platform sizes and capacities. No riders are allowed. Models may be floor mounted or pit mounted. Mechanical units are well suited to multiple level stops.*

**ISO 9001:2008  
Certified**



Min. Platform Size: 48 x 48 in.  
Max. Platform Size: 96 x 96 in.  
Lowered Height: 2.25 in.  
Overall Height: 110 + travel  
Overall Min. Width: 48 in.  
Overall Min. Depth: 64 in.  
Travel Max: 100 ft.  
Speed: 30 fpm.  
Horse Power: 4 HP



**2,000 lb. Capacity - 100' Travel**

## **SPECIAL FEATURES & BENEFITS**

- ▶ All of our controllers are assembled in our UL listed panel shop
- ▶ These units conform ASME B20.1
- ▶ These units also conform to VRC Guidelines – as referenced in ASME B20.1
- ▶ Motors are equipped with integral holding brakes
- ▶ All units have double chains
- ▶ The carriages also have mechanical locking brakes in case of chain failure